



# TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

## DAP® Wall Spray Texture: Knockdown Water Based

### PRODUCT DESCRIPTION



**DAP® Wall Knockdown Water Based** is an easy-to-use aerosol that provides excellent texture match. Its white, sag-resistant formula has strong wall adhesion, is paintable, and does not require priming. The grip trigger offers full hand control for an ergonomic spray. Fast dry time of 30 minutes depending on temperature, humidity & amount applied. Interior/Exterior.

PACKAGING	COLOR	UPC
20 oz can	White	7079850020

### KEY FEATURES & BENEFITS

- Adjustable for excellent texture match
- Control grip trigger
- 30-minute paint ready time depending on temperature, humidity & amount applied
- Strong adhesion – sag-resistant formula
- Texture and prime in one step
- Low odor
- Easy water clean-up

### SUGGESTED USES

#### USE FOR REPAIRING TEXTURED SURFACES:

- Drywall
- Stucco
- Plaster



# TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

## FOR BEST RESULTS

- **IMPORTANT:** Shake well before and frequently during spraying
- Cover surrounding areas to protect from over spray
- Apply in temperatures above 40°F
- Dispense a quick burst on scrap material to activate pressure
- Practice applying on scrap material before applying
- Spray using intermittent bursts
- Dip putty knife in water before each knockdown stroke
- Store away from direct heat in temperatures ranging from 40°F to 90°F
- While this formula does not require priming prior to paint application, priming may still be desired depending on your project/application requirements

## APPLICATION

### Surface Preparation

Surface must be clean, dry, structurally sound, and free of all foreign material. Make any necessary repairs to surface and ensure it is smooth and dry prior to applying spray texture.

### Product Application

1. **SHAKE** can upside down vigorously for more than a minute after hearing mixing marble moving freely in the can.
2. **TEAR OFF** top safety tab by pulling tab from front to back of top of nozzle. This safety tab is not reusable and it is meant to be broken off.  
**IMPORTANT:** Dispense a quick burst of material on scrap materials to activate pressure before applying to surface.
3. **ADJUST** texture for medium to heavy texture spray without straw insert. For heavier texture, overlap texture sprays. Adjust distance to the wall as necessary. For finer texture, firmly insert straw into nozzle tip. **IMPORTANT:** Practice using scrap material before applying onto the wall.
4. **SPRAY** holding can approximately 12 to 18 inches away from surface using intermittent bursts. For optimal blending, use different stroke motions like up and down, or left to right. Apply texture in overlapping passes to avoid gaps or uneven spots. If not satisfied, scrape-off and reapply. **IMPORTANT:** Be sure that the area is well ventilated and proper safety gear is worn.
5. **KNOCKDOWN** Allow spray texture to dry for 30 seconds (for fine texture) to 1 minute (for medium texture) and 1 to 2 minutes (for heavy texture). Hold putty knife parallel to the wall and lightly flatten knockdown to desired texture. **IMPORTANT** be sure to dip putty knife into water in between each knockdown.
6. **PAINT:** Allow texture to dry for 30 minutes prior to painting. Dry time may be longer in cooler/humid conditions or with thicker applications. Follow paint manufacturer's instructions for best results. For exterior applications, use exterior grade paint.



# TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

7. **CLEAN-UP** straw, nozzle, tools, and area with towel and warm water. Invert can point the top straight down. Spray a quick burst onto a disposable surface until texture is cleared from tip. Remove any texture build-up from the nozzle.
8. **STORE** at room temperature, avoid extreme cold or heat.

## TYPICAL PHYSICAL & CHEMICAL PROPERTIES

Typical Uncured Physical Properties	
Appearance/Consistency	White textured material
Base Polymer	Acrylic Latex
Weight % Solids	55.3%
Density (lbs per gallon)	11.5
Odor	Low odor
Clean Up	Water
Shelf Life	12 months
Coverage	Fine: up to 100 sq. ft. Medium: up to 70 sq. ft. Heavy: up to 55 sq. ft.
Typical Application Properties	
Application Temperature Range	Best between 65°F-80°F

## CLEAN UP & STORAGE

Uncured material can be cleaned up with soap and water. Excess cured material can be scraped off or sanded down.

## SAFETY

See product label and Safety Data Sheet (SDS) for health and safety information. You can request an SDS by visiting our website at [dap.com](http://dap.com) or by calling **888-DAP-TIPS**.

## LIMITED WARRANTY

**Limited Warranty:** If product fails to perform as directed within one year from the date of purchase, call 888-DAP-TIPS with your sales receipt and product container available for replacement product or sales price refund. DAP Global Inc. will not be responsible for incidental or consequential damages.



# TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

## COMPANY IDENTIFICATION

**Manufacturer:** DAP Global Inc., 2400 Boston Street, Suite 200, Baltimore, Maryland 21224

**Usage Information:** Call 888-DAP-TIPS or visit [dap.com](http://dap.com) & click on "Ask the Expert"

**Order Information:** 800-327-3339 or [orders@dap.com](mailto:orders@dap.com)

**Fax Number:** 410-558-1068

**Also, visit the DAP website at [dap.com](http://dap.com)**