



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

DAP® Wall Spray Texture: Orange Peel Water Based

PRODUCT DESCRIPTION



DAP® Wall Spray Texture Orange Peel Water Based is an easy to use aerosol that provides excellent texture match. Its white sag-resistant formula has strong wall adhesion, is paintable, and does not require priming. The grip trigger offers full hand control for an ergonomic spray. Fast dry time of 30 minutes depending on temperature, humidity & amount applied. Interior/Exterior.

PACKAGING	COLOR	UPC
20 oz can	White	7079850015

KEY FEATURES & BENEFITS

- Adjustable for excellent texture match
- 30 minute paint ready time depending on temperature, humidity & amount applied
- Strong adhesion – sag-resistant formula
- Texture and prime in one step
- Control grip trigger
- Low odor
- Easy water clean-up

SUGGESTED USES

USE FOR REPAIRING TEXTURED SURFACES:

- Drywall
- Stucco
- Plaster



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

FOR BEST RESULTS

- IMPORTANT: Shake well before and frequently during spraying
- Cover surrounding areas to protect from over spray
 - Apply in temperatures above 40°F
 - Dispense a quick burst on scrap material to activate pressure
 - Practice applying on scrap material before applying
 - Spray using intermittent bursts
 - Store away from direct heat in temperatures ranging from 40°F to 90°F
 - Texture formula includes primer for wall and paint adhesion, however paint manufacturer may still require the use of a primer and/or two coats depending on application and sheen

APPLICATION

Surface Preparation

Surface must be clean, dry, structurally sound and free of all foreign material.

Make any necessary repairs to surface and ensure it is smooth and dry prior to applying spray texture.

Product Application

1. **SHAKE** can upside down vigorously for more than a minute after hearing mixing marble moving freely in the can.
2. **TEAR OFF** top safety tab by pulling tab from front to back of top of nozzle. This safety tab is not reusable and it is meant to be broken off.
IMPORTANT: Dispense a quick burst of material on scrap materials to activate before applying to surface.
3. **ADJUST** texture: for medium to heavy texture, spray without straw insert. For heavier texture, overlap texture sprays. Adjust distance to the wall. For finer texture, firmly insert straw into nozzle tip. **IMPORTANT:** Practice using scrap material before applying onto the wall.
4. **SPRAY** holding can approximately 12 to 18 inches away from surface using intermittent bursts. For optimal blending, use different stroke motions like up and down, or left to right. Apply texture in overlapping passes to avoid gaps or uneven spots. If not satisfied, scrape-off and reapply. **IMPORTANT:** Be sure that the area is well ventilated and proper safety gear is worn.
5. **PAINT:** Allow Texture to dry for 30 minutes prior to painting. Dry time may be longer in cooler/humid conditions or with thicker applications. Follow paint manufacturer's instructions for best results. For exterior applications, use an exterior grade paint.
6. **CLEAN-UP** straw, nozzle, tools and area with towel and warm water. Be sure to remove any texture build up from tip/nozzle to prevent material drying on nozzle. Invert can pointing the top straight down. Spray a quick burst onto a disposable surface until texture is cleared from tip..
7. **STORE** at room temperature, avoid extreme cold or heat.



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

TYPICAL PHYSICAL & CHEMICAL PROPERTIES

Typical Uncured Physical Properties	
Appearance/Consistency	White textured material
Base Polymer	Acrylic Latex
Weight % Solids	54.6%
Density (lbs per gallon)	11.2
Odor	Low Odor
Clean-up	Water
Shelf Life	12 months
Coverage	Fine up to 100 sq. ft. Medium up to 70 sq. ft. Heavy up to 55 sq. ft.
Typical Application Properties	
Application Temperature Range	Best between 65F- 80F
Typical Cured Performance Properties	
Service Temperature Range	Above 40F



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

CLEAN UP & STORAGE

Uncured material can be cleaned up with water. Excess cured material can be scraped off or sanded down.

SAFETY

See product label and Safety Data Sheet (SDS) for health and safety information. You can request an SDS by visiting our website at dap.com or by calling **888-DAP-TIPS**.

LIMITED WARRANTY

Limited Warranty: If product fails to perform as directed within one year from the date of purchase, call 888-DAP-TIPS with your sales receipt and product container available for replacement product or sales price refund. DAP will not be responsible for incidental or consequential damages.

COMPANY IDENTIFICATION

Manufacturer: DAP Global Inc., 2400 Boston Street, Suite 200, Baltimore, Maryland

21224 **Usage Information:** Call 888-DAP-TIPS or visit dap.com & click on "Ask the

Expert" **Order Information:** 800-327-3339 or orders@dap.com

Fax Number: 410-558-1068

Also, visit the DAP website at dap.com