



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

DAP® Platinum Patch™ Advanced Exterior Filler

PRODUCT DESCRIPTION

DAP® PLATINUM PATCH™ Advanced Exterior Filler is formulated for the most demanding exterior home repairs with superior multi-material adhesion to the most common building materials including fiber cement & vinyl siding, PVC trim, composite decking, metal, mortar, wood, brick and more. It's formulated with advanced Weathermax Technology, providing exceptional weatherproof capabilities and UV protection to prevent color fading, discoloration, cracking, crumbling or other damage that could be caused from harsh weather. It's easy to apply, sandable and paintable and low in odor.



PACKAGING	COLOR	UPC
7 oz. (236 mL)	White	7079818786
16 oz. (473 mL)	White	7079818741
32 oz. (946 mL)	White	7079818787

KEY FEATURES & BENEFITS

- Weathermax Technology – Weatherproof and waterproof
- Lifetime Mold, Mildew and Algae Resistance Guarantee
- For the most demanding repairs
- Multi-Material Adhesion - Metal, Composite, PVC, Wood Vinyl & More
- Sandable & Paintable
- Ideal for exterior applications

SUGGESTED USES

Ideal for filling holes, cracks, dents and defects on Aluminum/Steel, Composite, PVC, Fiber Cement, Wood, Mortar, Concrete, Vinyl, Brick, Stucco, Plaster, Drywall and more.

FOR BEST RESULTS

- Do not apply when temperatures are below 40°F.
- Allow product to fully cure before exposing to water, approximately 24 hours.
- Do not use on floors or as a caulk, sealant or joint filler over cracks and joints where expansion and contraction may occur.



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

- **DO NOT USE AS A SKIM COAT.**
- A topcoat is not required, however, if desired, product can be painted with a high-quality latex-based paint.
- Staining is not recommended.
- Not for continuous underwater use.

APPLICATION

1. Surface must be free of grease, oil and other foreign matter. Sweep or blow surface with compressed air to remove all mud, dirt, dust and other loose debris.
2. Stir thoroughly before use.
3. Apply with a clean putty knife.
4. For a smoother finish, dip putty knife in water and lightly smooth spackling.
5. One application is usually sufficient for small repairs. For repairs deeper than 1/8", apply two or more layers allowing to dry between applications.
6. May be sanded and/or painted in 2 to 4 hours depending on temperature, humidity and depth of fill.
7. Wet sanding is recommended to avoid generation of dust.
8. Clean tools immediately with water.

TYPICAL PHYSICAL & CHEMICAL PROPERTIES

Consistency	Paste
Vehicle	Acrylic Latex
Volatile	Water
Filler	Inert Filler
Odor	Mild
Weight/Gallon	13 lbs./gallon
Solids	79%
Application Temperature	40°F to 150°F
Service Temperature	0°F to 120°F
Shelf Life	12 months
Freezing	Freeze/thaw stable 5 cycles at 0°F/ 8 hours at 73°F



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

Dry Time

2 to 4 hours depending on temperature, humidity and depth of fill

CLEAN UP & STORAGE

Wash tools immediately after use with water. Cured product must be cut or scraped away. Be sure container is closed and tightly sealed. Store container in a cool, dry place away from extreme heat or cold.

SAFETY

See product label and Safety Data Sheet (SDS) for health and safety information. You can request an SDS by visiting our website at dap.com or by calling **888-DAP-TIPS**.

WARRANTY

Limited Warranty:

If product fails to perform as directed, within one year from the date of purchase, call 888-DAP-TIPS, with your sales receipt and product container available, for replacement product or sales price refund. DAP Products Inc. will not be responsible for incidental or consequential damages.

COMPANY IDENTIFICATION

Manufacturer: DAP Products Inc., 2400 Boston Street, Baltimore, Maryland 21224

Usage Information: Call **888-DAP-TIPS** or visit dap.com & click on "Ask the Expert"

Order Information: 800-327-3339 or orders@dap.com

Fax Number: 410-558-1068

Also, visit the DAP website at dap.com